


Wiring Devices - Series 60309 Pin and Sleeve

Dual-Listed ■ Receptacles, Plugs and Connectors ■ ; ; 6h ■ Watertight

Dual-Listed Wiring Devices – 30A-100A / 32A-125A

The MENNEKES range of DUAL CERTIFIED Pin & Sleeve devices have agency approval for use in North America, European and International markets. One device fulfills multiple electrical needs to satisfy global equipment requirements for data centers and server equipment applications.

 Listed to UL1682/1686 and CSA 22.2 181.1, these products are also  Certified and have a  mark. Dual-Listed configurations are rated 30/32A, 60/63A and 100/125A – Offered in 3-Pole 4 wire and 4-Pole 5 wire in the 6 o'clock ground contact position, this range is fully intermateable with like-rate devices from other manufactures to support universal installation requirements.

MENNEKES Plugs and Connectors have threaded NPT cable entry for direct installation of flexible conduit fittings; costly adaptor fittings are not required. PowerTOP Xtra 60/63A and 100/125A parts feature Valox V-O rated threaded housing with a thermoplastic elastomer finish to enhance handling and facilitate installation. All devices are RoHS compliant with UL Type 4X and IP67 Rating. IP44 Weatherproof devices are also available upon request.



Wiring Devices - Series 60309 Pin and Sleeve

Dual-Listed ■ Receptacles, Plugs and Connectors ■ ; ; 6h ■ Watertight

Receptacles 30 Amp - 100 Amp / 32 Amp - 125 Amp



Dimension:
30/32A see page 13
60/63A see page 14
100/125A see page 15

Wire Configuration	AMP	Voltage	Catalog Number
3 Pole 4 Wire	30/32	380/415	ME 430R6W-L
4 Pole 5 Wire		200/346 240/415	ME 530R6W-L
3 Pole 4 Wire	60/63	380/415	ME 460R6W-L
4 Pole 5 Wire		200/346 240/415	ME 560R6W-L
3 Pole 4 Wire	100/125	380/415	ME 4100R6W-L
4 Pole 5 Wire		200/346 240/415	ME 5100R6W-L

Large Industry Standard Flange coming soon

Plugs 30 Amp - 100 Amp / 32 Amp - 125 Amp



60/63A and 100/125A Plugs: Pilot contact Standard.
* Available in splashproof. To order, omit W suffix.

Dimension:
30/32A see page 20
60/63A see page 21
100/125A see page 21

Wire Configuration	AMP	Voltage	Catalog Number
3 Pole 4 Wire	30/32	380/415	ME 430P6W
4 Pole 5 Wire		200/346 240/415	ME 530P6W
3 Pole 4 Wire	60/63	380/415	ME 460P6W-62334C*
4 Pole 5 Wire		200/346 240/415	ME 560P6W-62335C*
3 Pole 4 Wire	100/125	380/415	ME 4100P6W-62340C
4 Pole 5 Wire		200/346 240/415	ME 5100P6W-62357C

Connectors 30 Amp - 100 Amp / 32 Amp - 125 Amp



* Available in splashproof. To order, omit W suffix.

Dimension:
30/32A see page 22
60/63A see page 23
100/125A see page 23

Wire Configuration	AMP	Voltage	Catalog Number
3 Pole 4 Wire	30/32	380/415	ME 430C6W
4 Pole 5 Wire		200/346 240/415	ME 530C6W
3 Pole 4 Wire	60/63	380/415	ME 460C6W*
4 Pole 5 Wire		200/346 240/415	ME 560C6W*
3 Pole 4 Wire	100/125	380/415	ME 4100C6W
4 Pole 5 Wire		200/346 240/415	ME 5100C6W